

also all windows made tight with sheet lead.
 The columns to be made of 2 inch plank and fluted according to section with one flute in each stave or lug to be put together with white lead and well nailed. the caps to be glued up and turned in best manner good hard pine steps to side door with white pine or chestnut stringers.

Windows.

The window frames to have plank stools. parting strips and stop beads to finish outside with band mouldings and made for both to open: the sashes to be 1 $\frac{3}{8}$ in. thick and all to be furnished with a sufficient number of sash fastenings. the size of the glass to be as marked on the plans showing the openings all to be 12 lights excepting those in the privies which are to be 4 lights each. there are to be 16 sky lights in the roof each containing 20 lights of 7 by 9 glass with 2 inch sashes to be well hung and furnished with rods for raising and fastening 2 of the sky lights to be placed over the lofts the rest to open into the attic. the corner circular window to be glazed with glass to conform to the shape of the window to have good strong 2 inch sash and made to slide. all the sashes are to be glazed with No. 3 Redford glass and the sky lights to be glazed with 6. Redford glass all to be well puttied back and sprung.

Outside doors.

To be of sizes marked on plan to be 2 inches thickness paneled and moulded both sides and hung with 4 $\frac{1}{2}$ inch loos joint butts 3 pairs on each of the double doors the standing part of double doors to be furnished with slide bolt at bottom and spring bolt and chain at the tops and each to be furnished with a strong store lock worth on an average \$4. each.

Floors.

the inside floors are to be composed of sound clear and dry hard pine boards 1 $\frac{1}{8}$ inches thick when worked to be well wrought tunged and grooved and well nailed with 12 penny nails none of the boards are to be oversix inches in width and all to be free from loose knots and shakes the top floor of the basement to have square edges. The piazza floor or platform floor outside is to be composed of sound and clear